




MOTOWELD 200



HONDA GX270 OHV



4,5 kVA



170 A



Sockets
x1 16A, 400V-50Hz~3ph EEC
x1 16A, 230V-50Hz~1ph EEC



12V DC
Battery Charger Outlet



Earth Leakage
Circuit Breaker



Low Oil Level



Power Output
Protection



70dB at 7 m



START MANUAL
RECOIL



AIR COOLING

Benzina
 Essence
 Petrol



Gasolina
 Benzin
 бензин

AWS E6013
 AWS E7018
 AWS E308
 AWS A5.15

OPTIONAL ON DEMAND (OEM)

welding cable
Ø25mm² (5+3m)
with accessories

Technical specifications

GENERATOR			
Asynchronous self-protected self excited	230V~1ph 400V~3ph 50Hz AC	3 kVA 4,5 kVA	cos φ 0,8

ENGINE						
HONDA GX270	3000	1Cyl/270cc	9 hp (6 kWm)	@75%: 2,2 l/h	5,3 l	LWA 95

DC WELDING				
No load voltage	Welding current	Duty cycle 35%	Duty cycle 60%	Electrodes
90	40-170	35/170	60/140	1,6-4mm

ACCESSORIES & CONSUMABLES					
Order code	Volume	PCS per Euro pallet	Weight	Size (mm)	Bar code
MOTOWELD 200	63550	0,18m ³	8	94 kg dry 720x480x515	8004386635506